

Description: Unsupported light weight nitrile glove with excellent resistance to ketones, diluted solvents and methanol

- Features & Benefits:
- * Exceptional chemical protection against a wide range of ketones, ketone water mixtures, strong solvents and alcohols
 - * Lighter weight to offer high dexterity and sensitivity
 - * Can be used in high humid conditions and resistant to water splashes
 - * Anatomically shaped for comfort
 - * Free of latex allergy

Applications: Handling of ketones in laboratories, Ink and paint industries, Manufacture of plastics, Metal treatment using solvents, Printing Industry, Manufacturing of gums, resins and composite materials, (Limitations - Not recommended to use with water for prolong periods)

Limitations: Not recommended to use with water for prolonged periods

Elastomer: Nitrile rubber with a modified PVA coating

Thickness: 0.28 +/- 0.02 mm

Lining: Unlined

Former: Plain

Exterior: Smooth finish

Cuff Types: Straight

Treatments: Un-chlorinated

Colours: Blue B14

CE Certification: Conforms to PPE Regulation EU 2016/425 to (Complex Design) Personal Protective Equipment after assessment against standards EN 374-1:2016, EN 374-4:2013, EN 388:2016 and EN 420:2003+A1:2009

Conforms to: ASTM D4679 of 2002

Physical Dimensions:	Size	Palm	Wrist	Cuff	Length
	7	206	202	302	330
	8	222	220	306	330
	9	239	228	328	330
	10	260	252	342	330
	11	275	268	349	330

Circumference in mm, +/- 5 mm Fol. +/- 10 mm

Protection against Chemical hazards

Performance

Degradation %

EN 374



- * Dichloromethane (D)
- * Diethylamine (G)
- * Ethyl acetate (I)
- * Isopropanol
- * Methanol (A)
- * Methyl Ethyl Ketone
- * n-Heptane (J)
- * n-hexane
- * Acetone (B)
- * Toluene (F)
- * Xylene
- * Ethanol, 99.9%
- * Acetone:Water (50:50) mixture

Level 5	X
Level 3	X
Level 6	X
Level 6	X
Level 2	X
Level 6	X
Level 6	X
Level 6	X
Level 6	X
Level 6	X
Level 4	X
Level 2	X


Note: Printed copies are valid only on the date printed

Printed Date: 07-Jan-2020

Revision: 1

Published Date: 19-Jul-2019

Protection against Mechanical hazards Performance

EN 388	* Abrasion resistance	Level 3
	* Blade cut resistance	Level 0
	* Puncture resistance	Level 1
	* Tear resistance	Level 0

Protection against Micro-organisms risk Performance

EN 374	* Air leak test	Passed
	* Water leak test	Passed